

AT

NAME	ADDRESS	CITY	STATE	ZIP
Mr. J. H. Jones	1234 Main St.	Springfield	Ill.	62760
Mr. W. R. Smith	5678 Oak Ave.	Chicago	Ill.	60640
Mr. T. L. Brown	9012 Elm St.	Peoria	Ill.	61602
Mr. G. M. Davis	3456 Maple Dr.	Rockford	Ill.	61101
Mr. K. N. Wilson	7890 Cedar Ln.	Decatur	Ill.	62521
Mr. P. Q. Taylor	2345 Birch St.	Normal	Ill.	62450
Mr. R. S. White	6789 Pine Ave.	Urbana	Ill.	62501
Mr. V. T. Green	1011 Spruce St.	Macomb	Ill.	61456
Mr. Y. U. Black	4321 Ash Dr.	Quincy	Ill.	62401
Mr. Z. V. Gray	8765 Willow Ln.	East St. Louis	Ill.	60620
Mr. A. W. Hall	2109 Hickory St.	Alton	Ill.	62002
Mr. B. X. King	5432 Sycamore Ave.	Granite City	Ill.	62040
Mr. C. Y. Lee	9876 Chestnut St.	Edwardsville	Ill.	62025
Mr. D. Z. Scott	3210 Walnut Dr.	Shelbyville	Ill.	62951
Mr. E. A. Adams	7654 Mulberry Ln.	St. Louis	Mo.	63101
Mr. F. B. Baker	1098 Poplar St.	St. Charles	Mo.	63071
Mr. G. C. Carter	4567 Magnolia Ave.	St. Joseph	Mo.	64501
Mr. H. D. Evans	8901 Dogwood Dr.	Warrensburg	Mo.	64080
Mr. I. E. Foster	2345 Redwood Ln.	Springfield	Mo.	65801
Mr. J. F. Gibson	6789 Cypress St.	Branson	Mo.	64601
Mr. K. G. Harris	1011 Juniper Ave.	Jefferson City	Mo.	64501
Mr. L. H. Ingram	4321 Fir St.	St. Louis	Mo.	63101
Mr. M. I. Jackson	8765 Hemlock Dr.	St. Charles	Mo.	63071
Mr. N. J. Keller	3210 Laurel Ln.	St. Joseph	Mo.	64501
Mr. O. K. Lewis	7654 Alder St.	Warrensburg	Mo.	64080
Mr. P. L. Miller	1098 Hawthorn Ave.	Springfield	Mo.	65801
Mr. Q. M. Nelson	4567 Boxwood Dr.	Branson	Mo.	64601
Mr. R. N. Owen	8901 Yew St.	Jefferson City	Mo.	64501
Mr. S. O. Parker	2345 Sassafras Ln.	St. Louis	Mo.	63101
Mr. T. P. Quinn	6789 Dogwood Ave.	St. Charles	Mo.	63071
Mr. U. R. Reed	1011 Redwood St.	St. Joseph	Mo.	64501
Mr. V. S. Russell	4321 Cedar Dr.	Warrensburg	Mo.	64080
Mr. W. T. Scott	8765 Elm Ln.	Springfield	Mo.	65801
Mr. X. U. Stone	3210 Maple St.	Branson	Mo.	64601
Mr. Y. V. Thomas	7654 Oak Ave.	Jefferson City	Mo.	64501
Mr. Z. W. Turner	1098 Pine St.	St. Louis	Mo.	63101
Mr. A. X. Walker	4567 Birch Dr.	St. Charles	Mo.	63071
Mr. B. Y. Young	8901 Cedar Ln.	St. Joseph	Mo.	64501
Mr. C. Z. Allen	2345 Elm St.	Warrensburg	Mo.	64080
Mr. D. A. Wright	6789 Maple Ave.	Springfield	Mo.	65801
Mr. E. B. King	1011 Oak Dr.	Branson	Mo.	64601
Mr. F. C. Green	4321 Pine St.	Jefferson City	Mo.	64501
Mr. G. D. White	8765 Cedar Ln.	St. Louis	Mo.	63101
Mr. H. E. Black	3210 Elm Ave.	St. Charles	Mo.	63071
Mr. I. F. Gray	7654 Maple St.	St. Joseph	Mo.	64501
Mr. J. G. Hall	1098 Oak Dr.	Warrensburg	Mo.	64080
Mr. K. H. King	4567 Pine Ln.	Springfield	Mo.	65801
Mr. L. I. Lee	8901 Cedar St.	Branson	Mo.	64601
Mr. M. J. Miller	2345 Elm Ave.	Jefferson City	Mo.	64501
Mr. N. K. Nelson	6789 Maple St.	St. Louis	Mo.	63101
Mr. O. L. Owen	1011 Oak Dr.	St. Charles	Mo.	63071
Mr. P. M. Parker	4321 Pine Ln.	St. Joseph	Mo.	64501
Mr. Q. N. Quinn	8765 Cedar St.	Warrensburg	Mo.	64080
Mr. R. O. Reed	3210 Elm Ave.	Springfield	Mo.	65801
Mr. S. P. Russell	7654 Maple St.	Branson	Mo.	64601
Mr. T. Q. Scott	1098 Oak Dr.	Jefferson City	Mo.	64501
Mr. U. R. Stone	4567 Pine Ln.	St. Louis	Mo.	63101
Mr. V. S. Thomas	8901 Cedar St.	St. Charles	Mo.	63071
Mr. W. T. Turner	2345 Elm Ave.	St. Joseph	Mo.	64501
Mr. X. U. Walker	6789 Maple St.	Warrensburg	Mo.	64080
Mr. Y. V. Young	1011 Oak Dr.	Springfield	Mo.	65801
Mr. Z. W. Allen	4321 Pine Ln.	Branson	Mo.	64601
Mr. A. X. Wright	8765 Cedar St.	Jefferson City	Mo.	64501
Mr. B. Y. King	3210 Elm Ave.	St. Louis	Mo.	63101
Mr. C. Z. Green	7654 Maple St.	St. Charles	Mo.	63071
Mr. D. A. White	1098 Oak Dr.	St. Joseph	Mo.	64501
Mr. E. B. Black	4567 Pine Ln.	Warrensburg	Mo.	64080
Mr. F. C. Gray	8901 Cedar St.	Springfield	Mo.	65801
Mr. G. D. Hall	2345 Elm Ave.	Br		

5

10

15

20

25

pedals are closer to the driver. A shorter driver, who moves the driver's seat closer to the steering wheel and higher up, will maneuver the pedals more from above than is the case with a tall driver who lowers the driver's seat and moves it away from the steering wheel.

Thus, it would be desirable to provide an adjustable pedal assembly that includes horizontal adjustment, i.e., adjustment in fore and aft directions with respect to the vehicle, and which includes angular adjustment of the pedal pads so that the pads can be angled upwardly when the pedals are closer to the driver. It is important that this pedal assembly include a drive arrangement for selectively adjusting pedal position that can be easily integrated in the vehicle. It is also desirable for the adjustable pedal assembly to be designed such that if the vehicle is in a collision, the pedal components will not come into contact with the driver. Finally, the adjustable pedal assembly should be simpler in design and less expensive than prior art pedal assemblies.

SUMMARY OF THE INVENTION AND ADVANTAGES

An adjustable pedal assembly includes a mounting arrangement for attachment to a vehicle structure and at least one pedal pivotally supported with respect to the mounting structure. The pedal pivots about a first pivot axis. An adjustment element is pivotally supported with respect to the mounting structure and defines a second pivot axis. The adjustment element selectively moves the pedal between a plurality of operable positions. The assembly is characterized by the pedal being pivotally supported with respect to the adjustment element wherein the second pivot axis is generally parallel to the first pivot axis.

BRIEF DESCRIPTION OF THE DRAWINGS

Other advantages of the present invention will be readily appreciated as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings wherein:

Figure 1 is a perspective view of the subject adjustable pedal assembly;

Figure 2 is a front view of the adjustable pedal assembly shown in Figure 1;

and

Figure 3 is a side view of the adjustable pedal assembly shown in Figure 1.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to the Figures, wherein like numerals indicate like or corresponding parts throughout the several views, an adjustable pedal assembly is shown in Figure 1. The invention will be described below using directional and positional indications. These indications concern the conditions that prevail when the object of the invention is mounted in a vehicle. Thus, indications such as "left," "right," "forward (fore direction)," "rearward (aft direction)," etc. in the application concern corresponding indications as normally used in connection with a vehicle and should not be considered limiting.

In Figure 1, reference number 1 generally concerns a mounting arrangement by which the adjustable pedal assembly is mounted to a vehicle structure 37. The mounting arrangement 1 is designed and situated to provide a securing of the pedal assembly in a special supporting bar that is separate from a vehicle cowl so that the pedal assembly is not affected by such movements that the cowl might make during a collision. The mounting arrangement 1 which thus will be designated as stationary relative to the vehicle, is comprised of a first fastening element 2 and a second fastening element 3 with fastening points 23 and 24 as well as 25 and 26, respectively. The two (2) fastening elements 2 and 3 have supports that define a pivot axis 4. Any type of fasteners known in the art can be used to fasten the fastening elements 2, 3 to the vehicle structure 37 at fastening points 23, 24, 25, 26.

The object of the invention also includes an adjustment element that is generally designated by 5. The adjustment element 5 is connected to the mounting arrangement 1 and is pivotal relative to the mounting arrangement about the pivot axis 4.

The adjustment element 5 serves to fasten and support a plurality of pedals 6, 7, 8 which are supported by the mounting arrangement 1. Each of the pedals 6, 7, 8 is connected to an actuator that is used to control a vehicle system. This will be discussed in greater detail below.

Preferably, pedal 8 is a clutch pedal used to activate a clutch mechanism for shifting gears within a vehicle. Pedal 7 is preferably a brake pedal used to activate a vehicle braking system and pedal 6 is preferably an accelerator pedal used to activate an engine throttle. While three (3) pedals 6, 7, 8 are shown, it should be understood that the adjustable pedal assembly could include more or less pedals. Each of the pedals 6, 7, 8 extends downwardly from the adjustment element 5 and

terminates at a pedal pad 30, 31, 32, respectively. The pedal pads 30, 31, 32 are attached to free ends of the pedals 6, 7, 8 and are adapted to receive the driver's foot.

5 The pedals 6, 7, 8 are pivotally supported in the adjustment element 5 and are pivotal around a common pivot axis 9, which is shown in Figure 1. The two (2) pivot axes 4 and 9 are essentially parallel to each other, and are approximately horizontal and crosswise relative to the longitudinal direction of the vehicle.

10 As an alternative to the common pivot axis 9 for the three (3) pedals 6, 7, 8, it is possible that each of the pedals 6, 7, 8 could be suspended around two or possibly three pivot axes separated from each other. In this embodiment also, the pivot axes are approximately parallel to each other, and are generally horizontal and orientated crosswise relative to the longitudinal direction of the vehicle.

15 It is evident from the view in Figure 3, which shows the adjustable pedal assembly from the side, that the pivot axis 9 for the pedals 6, 7, 8 is located beneath and in front of the pivot axis 4 for the adjustment element 5. Because the pedals 6, 7, 8 in the unactuated state are spring-tensioned to stop positions in the clockwise direction around the pivot axis 9, it is evident that with the pivoting of the adjustment element 5 around the pivot axis 4, the adjustment element 5 and the pedals 6, 7, 8 suspended on the adjustment element 5 will move as a rigid unit.

20 Figure 3 shows the pedals 6, 7, 8 with solid lines in the unactuated state and in an initial position before such a pivoting and with dashed lines in the unactuated state after such a pivoting. In other words, the solid lines show the position of the pedals 6, 7, 8 at their furthest position from the driver before they are pivoted as a unit about pivot axis 4 and the dashed lines show the position of the pedals 6, 7, 8 after they have been pivoted as a unit about pivot axis 4 and where the pedals 6, 7, 8 are in their closest position to the driver. It is evident from Figure 3 that as the pedals 6, 7, 8 were pivoted about pivot axis 4, the pedal pads 30, 31, 32 were shifted rearwardly in the longitudinal direction of the vehicle to a considerable extent. Additionally, as the pedals 6, 7, 8 were pivoted about pivot axis 4, the pedal pads 30, 31, 32 were angled upwardly at an angle that is as great as the angle of rotation for the adjustment element 5 around the pivot axis 4. The pedal pads 30, 31, 32 are also
30 lifted to a higher level.

In the example shown, the longitudinal shift of the pedal pads can be up to 100 mm with a pivot angle of about 18° around the pivot axis 4 at the same time as the pedal pads 30, 31, 32 are lifted about 20 mm. A corresponding angling up of the

pedal pads 30, 31, 32 is also effected. The position of the pivot axis 9 of the pedals 6, 7, 8 in the example illustrated means that in the initial position according to the drawing, an angle is formed between a vertical line 34 through the pivot axis 4 and a connecting line 35 between the pivot axis 4 and the pivot axis 9 of approximately 35°. It should be understood that the numerical quantities for the horizontal, vertical, and angular adjustments discussed above, are exemplary in nature and are not limiting.

Sub. B1
10
A driving mechanism is used to selectively move the adjustment element 5 about the pivot axis 4. In the fastening element 2 of the mounting arrangement 1, shown in Figure 2, a stator element 10 is attached to an angular gear assembly that can be selectively driven under the effect of an electric drive motor 11. The angular gear assembly has a rotor element 12^{which} that rotates with respect to the stator 10, seen in Figure 1, and which is supported on the fastening element 2 to drive the adjustment element 5. Thus, with the rotation of the rotor element 12, the adjustment element 5 will follow the movement and hence pivot about the pivot axis 4.

15
The angular gear assembly is designed as a planetary gear that is self-braking and designed to handle very large rotational torques on the order of 1000 Nm (Newton-meters) or more. Thus, no locking element is required for locking the adjustment element 5 in the selected adjustment position. The gear assembly is also extremely compact in its outer dimensions which improves packaging.

20
As an alternative to the angular gear, a linear adjusting device can be coupled to a connecting element 15 that extends between fastening element 2 and fastening element 3, and which is located at a distance from the pivot axis 4. Optionally the linear adjusting device can be connected to an element that is non-rotationally connected to the connecting element 15.

25
Sub. B2
30
To summarize, the the pedals 6, 7, 8 in the adjustable pedal assembly are pivotally supported with respect to the adjustment element 5 wherein the second pivot axis 4 is generally parallel to the first pivot axis 9. The driving mechanism with the electric motor 11 and gear assembly 12 is used to selectively rotate the adjustment element 5 about the second pivot axis 4. The pedals 6, 7, 8 are pivotally mounted within the adjustment element 5 to pivot about the first pivot axis 9, thus the position of the first pivot axis 9 moves with respect to the second pivot axis 4 when the adjustment element 5 is rotated.

B4
Cont

~~the upwardly directed arm 20 the brake pedal 7 will be swung forward (away from the driver) if the drag link 22 should be shifted rearwardly (toward the driver) during a vehicle collision. This will prevent the brake pedal 7 from coming into contact with the driver during a vehicle collision.~~

Sub 5
B5

~~To make the brake function independent of the pivoting of the adjustment element 5 around the pivot axis 4, the drag link 22 is located in the forward end position of the pedals 6, 7, 8 over a connection line between the pivot axis 4 and the forward fastening of the drag link 22 in the brake servo. With a counter-clockwise pivoting of the adjustment element, as seen in Figure 3, such that the pedals 6, 7, 8 are shifted rearwardly in the vehicle, the drag link will pass down on the underside of the connection line. Suitably, the drag link 22 is located symmetrically around the connection line in the two extreme positions of the pedals 6, 7, 8.~~

10

The maneuvering device designed as a piston/cylinder unit 18 for the clutch pedal 8 can be omitted and replaced with an arrangement of the type described above

15

in connection with the brake pedal 7. It is also conceivable to use a hydraulic transfer with the brake pedal 7 of the type describe in connection with the clutch pedal 8. With regard to the accelerator pedal 6, a mechanical connection such as a wire or cable, can be used as an alternative to the electrical transfer described above.

20

The invention has been described in an illustrative manner, and it is to be understood that the terminology which has been used is intended to be in the nature of words of description rather than of limitation.

25

Obviously, many modifications and variations of the present invention are possible in light of the above teachings. It is, therefore, to be understood that within the scope of the appended claims, wherein reference numerals are merely for convenience and are not to be in any way limiting, the invention may be practiced otherwise than as specifically described.